



McCORRY & CO. LIMITED

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong

USA Fax: (1-810) 885-7051 Email: info@mccorry.com

1 PANEL PRODUCTS

Product type	Species	Origin	Thickness	Sizes	Quality & Grade	Glue Type	Type of Finish	Fumigation
Plywood	Hardwood and Softwood	Asia, South America and Europe	Ranging from 2.5mm to 30mm	1. 1220mm x 2440mm (4' x 8') 2. 915mm x 2135mm (3' x 7') 3. 1220mm x 2745mm (4' x 9') 4. 1220mm x 3050mm (4' x 10') 5. 1250mm x 2450mm 6. According to customer requirement	IHPA- JPIC- JAS- BS Standard	MR LFE MELAMINE WBP	According to customer requirements	Phytosanitary Certification can be arranged
FramePly	Birch face and back with a poplar core	China	12mm to 25mm	1220mm x 2440mm	IHPA Standard	MR	Repaired face and back for interior applications	
Laminply	Meranti	Asia	12mm to 18mm	1220mm x 2440mm	IHPA Standard JPIC Standard	MR	According to customer requirements. Can supply either vertical core or horizontal core	
Door Skin Plywood	Meranti	Asia	2.7mm to 3.6mm	According to customer requirements	IHPA Standard	MR LFE	According to customer requirements	
Blockboard or Lumbercore plywood	Meranti or other tropical hardwoods	Asia	12mm to 25mm	1220mm x 2440mm	IHPA Standard JPIC Standard	MR	Plain, Laminated or Fancy Face on one face or both faces	
Fancy Plywood	Temperate Hardwoods as requested	Asia	3.0mm to 18mm	1220mm x 2440mm	IHPA Standard NHLA Standard	MR LFE	Standard	
Concrete plywood	Hardwood with Film Face	Asia	12mm to 30mm	1220mm x 2440mm	IHPA Standard JPIC Standard	WBP MR	With a Black or Brown Film. Weight of film as per customer requirement	
Veneer	Hardwood and Softwood	Asia	0.6 to 4.2mm	1. 1220mm x 2440mm 2. 2440mm x 1220mm	IHPA Standard		Long Grain and Short Grain	
Fiberboard	Hardwood and Softwood	Asia	2.5mm to 30mm	1. 1220mm x 2440mm 2. 1830mm x 3660mm 3. 1830mm x 2440mm	According to customer requirement	MR E0 E1 E2	Plain, Finish Foil Lamination or Melamine Lamination	
Moulded Door Skin Panels	MDF or HDF	Asia	3mm to 4.8mm	1. 648mm x 2125mm 2. 749mm x 2125mm 3. 851mm x 2125mm 4. 952mm x 2125mm 5. 1220mm x 2440mm	According to customer requirement	MR E0 E1 E2	According to manufacturer's standard designs	



McCORRY & CO. LIMITED

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong
 USA Fax: (1-810) 885-7051 Email: info@mccorry.com

2 SAWN TIMBER

Product type	Species	Origin	Treatment	Sizes	Seasoning	Quality	Machining	Packing
Hardwood (Tropical)	Meranti, Kempas, Tualang, Keruing, Selangan Batu, Kapur, Red OT, Angelim Pedra, Greenheart, Mora, Bulletwood, Andiroba, Jatoba, Iteballi, Cumaru, Cumala, Shibadan, Wamara, Soft Wallaba, Purpleheart, etc	South East Asia and South America	Anti-stain and anti-fungus	Based on customers' requirement	AD with MC below 25% or KD with MC 8 - 16%	a) Select & Better grade b) Standard & Better grade c) Merchantable Grade In accordance with Malaysian Grading Rules 1984 or as According to customer requirement	Rough Sawn or surfaced (S2S or S4S)	ISPM-15 standard
Hardwood (Temperate)	Birch and Alder	Russia	Anti-stain and anti-fungus	Based on customers' requirement	AD or KD	GHOST standard (Export Grade as per Russian international grading rules)	Rough Sawn or Machined	
Softwood	Spruce, Fir, Larch and Pine	Russia, South America and Africa	Anti-stain and anti-fungus	Based on customers' requirement.	AD or KD	GHOST standard (Export Grade as per Russian international grading rules) and US standard	Rough Sawn or Machined	



McCORRY & CO. LIMITED

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong

USA Fax: (1-810) 885-7051 Email: info@mccorry.com

3 SEMI FINISHED PRODUCTS

Product type	Species	Origin	Sizes	Seasoning	Quality	Machining	Packing	Finish
Kiln Sticks	Medium Hardwood to Heavy Hardwood	South East Asia and South America	Based on Customers requirement	AD or KD	Standard grade according to MGR 1984	Surfaced and/or Ripped	ISPM-15 standard	S4S, or S2S and Multi RipS4S, E4E with radius 1/4" Moulded profile (fluted)
Stakes	Medium Hardwood to Heavy Hardwood	Malaysia and South America	Based on Customers requirement	Air dried. Well seasoned.	Standard Grade according to MGR 1984	Smooth band saw or multi ripped saw. One end with pencil point or 2 wedges-point or 4-wedges point.	AQIS or ISPM-15 Standard	Painted or Unpainted
Posts – Dowelled	Pine: Pinus Elliotti and Pinus Taeda	South America	Diameter: 6 cm to 12 cm Length: 2 m to 4 m	AD, well seasoned with MC below 25%	Tolerances on length: -0.0 cm / + 0.5 cm Tolerances on diameter: - 0.1 cm / + 0.2 cm No bark allowed No big knots allowed that influences the mechanical resistance of the poles.	Dowelled	Loose or in bundles	



McCORRY & CO.

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong

USA Fax: (1-810) 885-7051 Email: info@mccorry.com

4 MOULDINGS

Product type	Species	Origin	Sizes	Seasoning	Quality	Machining	Packing	Finish
Flooring Blanks	Ipe, Jatoba, Cumaru, Massaranduba, Tatajuba, Tauari, etc	South America	19mm x 100mm x 600mm /750mm (max. 30%) and 900mm (min. 70%) 19mm x 130mm x 600mm/750mm (max. 30%) and 900mm (min. 70%)	KD to MC 10 % - 12 %	S4S, Premium Grade according to Tropical Hardwood Machined Lumber Products Grading Rules. (THMLPGR) of 1987	S4S	ISPM-15 Standard	
Truck Flooring/ Shiplap	Keruing, Kapur	Malaysia, Indonesia, Laos	Based on customer requirement	KD to 12-14%	General Mouldings, Standard Grade according to Tropical Hardwood Machined Lumber Products Grading Rules. (THMLPGR) of 1987	Based on customer requirement	ISPM-15 Standard	Shiplap profile, S4S E4E or Tongue & Groove profile
Decking	Kapur, Yellow Balau ,Merbau, Ipe, Cumaru, Greenheart, Massaranduba, etc	Asia and South America	Based on customer requirement	KD to less than MC 18%	General Mouldings, Standard Grade according to Tropical Hardwood Machined Lumber Products Grading Rules. (THMLPGR) of 1987	S4S E4E or moulding profile according to customer requirement	ISPM-15 Standard	Based on customer requirement



McCORRY & CO. LIMITED

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong

USA Fax: (1-810) 885-7051 Email: info@mccorry.com

5 MILLWORK

Product type	Species	Origin	Sizes	Priming	Seasoning	Quality	Machining	Packing	Finish
Balusters	Rubber wood and or other suitable species	South East Asia	Diameter: 1-1/4" or as per customer requirement Length: 31" / 34" / 36" / 39" / 41"	Base primer	KD to 8-10%	General Mouldings, Standard Grade according to Tropical Hardwood Machined Lumber Products Grading Rules. (THMLPGR) of 1987	Turned and sanded	ISPM-15 Standard	Non-glossy or glossy white.
Flat Jambs	Pine or Mixed Light Hardwoods.	South East Asia and South America	Based on customer requirement	White Primer or Gesso	KD to 8-12%	General Mouldings, Standard Grade according to Tropical Hardwood Machined Lumber Products Grading Rules. (THMLPGR) of 1987	Finger joint and Edge-Glued Substrate allowed. Edges can back bevelled With Dado or without	ISPM-15 Standard	Natural or primed



McCORRY & CO. LIMITED

3905 Two Exchange Square, Suite 3756, 8 Connaught Place, Central, Hong Kong
USA Fax: (1-810) 885-7051 Email: info@mccorry.com

6 LOGS

Species	Origin	Sizes	Quality	Finish
Pine, Birch, Spruce, Larch, etc	Canada, Russia, Africa, New Zealand and South America	Based on customer requirement	a) Saw Logs b) Peeler Logs c) Pulp Grade Grades as per grading rules of the country of origin	Debarked or not debarked